



Product Information: Geartech MTF 75W

Description

Geartech MTF 75W is a high quality manual transmission fluid, manufactured from the highest quality fully synthetic base fluids and a tailored high performance additive system. The product exhibits outstanding low temperature performance, offering superior anti-wear protection and smooth operation from start-up. The product displays excellent thermal and oxidation stability, as well as offering outstanding protection from rust and corrosion and excellent anti-foaming behaviour.

Applications

Geartech MTF 75W is suitable for use in manual transmissions included synchronised transmissions where a fluid of this quality, performance level and viscosity is recommended by the original equipment manufacturer.

Performance Features

- Outstanding low temperature performance
- Thermally stable
- Resistant to oxidation
- Long service life
- Excellent wear protection
- Protection against rust and corrosion
- Excellent anti-foaming behaviour
- Compatible with seal materials

Performance Levels

- API GL-4
- Ford WSS-M2C200-D2
- VW TL 521 71 (G 052 171)
- VW TL 521 78 (G 052 178)
- VW TL 525 12 (G 052 512)
- VW TL 525 27 (G 052 527)
- VW TL 527 26 (G 052 726) Replaced by TL 607 26
- VW TL 607 26 (G 060 726)
- VW TL 707 26 (G 070 726)

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.867
Kinematic Viscosity @ 40°C	cSt	38.8
Kinematic Viscosity @ 100°C	cSt	6.8
Viscosity Index		138
Flashpoint (Closed)	°C	220
Pour Point	°C	-48

Figures based on average production values



Made in the
United Kingdom
Since 1925

Issue 1 September 2017

The above information is supplied to the best of our knowledge and belief on the basis of current industry and our own development work. Subject to amendment