

## Product Information: Select XL 20W-50

### Description

Select XL 20W-50 is a very high-quality, low detergent/dispersant multigrade engine lubricant, formulated utilising highly refined mineral base stocks and carefully selected performance additives. The product contains desirable levels of ZDDP and exhibits excellent resistance to wear. The carefully selected additives offer superior resistance to corrosion and exceptional control over piston deposits, soot and sludge. The product displays high shear stability and offers enhanced cold flow characteristics and control over foam, as well as been thermally stable and offering excellent resistance to oxidation and corrosion.

### Applications

Select XL 20W-50 is recommended primarily for naturally aspirated four stroke petrol and diesel engines found in classic passenger cars, motorcycles, commercial vehicles and tractors manufactured post 1960 up to the late 1970's or where a lubricant of this performance level and quality is specified by the original equipment manufacturer.

### Performance Features

- Excellent protection against wear
- Protection against corrosion
- Thermally stable
- Enhanced cold flow characteristics
- Excellent foam control
- Resistant to oxidation
- Control over piston deposits, soot and sludge
- High Shear stability

### Performance Levels

API SE/CC

### Typical Data

Characteristic	Unit	XL 20W-50
Density @ 15.6°C	kg/l	0.870
Kinematic Viscosity @ 40°C	cSt	154
Kinematic Viscosity @ 100°C	cSt	18.4
Viscosity Index		134
Flashpoint (Open)	°C	210
Pour Point	°C	-33

Figures based on average production values